

SEYPOS DT6800U

Lector Imager Omnidireccional

El nuevo lector SEYPOS DT6800U destaca por su potente motor de lectura imager de códigos 1D, 2D y PDF y por su elegante y resistente diseño, lo que le convierte en un escáner idóneo para puntos de venta, funciones “check-out”, lectura de códigos en dispositivos móviles como smartphones y tablets y para distintos sectores como el sanitario o la banca.



ID - 2D
PDF

Res.
4 mil

Múltiples
Interfaces

Auto
Sensor

Manos
Libres

- OMNIDIRECCIONAL • RESISTENTE
- ECONÓMICO • ÁNGULO AJUSTABLE



Nominal Working Range	
CODE 39	4mil 0 ~ 10cm
EAN13	10mil 0 ~ 21cm
EAN13	13mil 0 ~ 25cm
PDF417	10mil 0 ~ 18cm
Data Matrix	10mil 0 ~ 6cm
QR Code	10mil 2 ~ 6cm

Resolution: 4 mil
Performance may be impacted by bar code quality and environmental conditions

Características Técnicas Seypos DT6800U

Interface	HID USB / USB COM /RS-232
Códigos 1D	UPC/EAN/(UPCA/UPCE/UPCE1/EAN-8/EAN-13/JAN-8/JAN-13 plus supplemental, ISBN, ISSN, Coupon Code), Code 39, Code 39 Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128, (Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated), Code 93, Codeabar/NW7, Interleaved 2 of 5, Discrete 2 of 5, IATAChinese 2 of 5, Matrix 2 of 5, Code 11), MSI Plessey, GS1Databar, (Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked)
Códigos PDF417 (y variantes)	PDF417 (Standard, Macro), MicroPDF417 (Standard, Marco), Composite Code (CC-A, CC-B, CC-C)
Códigos 2D	MaxiCode, Data Matrix, Data Matrix inverse, QR Code, QR Inverse, Micro QR Code, Aztec Code, Aztec Inverse, Postal Code
Sistema Óptico	752 H x 480 V pixels (Wide VGA)
Fuente de Luz	Aiming Pattern: single dot, 625nm LED / Illumination: 630nm LEDs)
Resolución	4 mil (Code 39), 7.5 mil (Data Matrix), 5 mil (PDF 417)
Distancia de Lectura	Hasta 267 mm
Campo de Visión	Horizontal: 46.1°; Vertical: 30.4°
Indicadores	LEDs, Beeper
Voltaje	DC 5V
Consumo	<260mAr
Temperatura Operacional	0 °C to 40 °C (32°F to 104°F)
Humedad Operacional	5% ~95% RH(non-condensing/non-freezing)
Resistencia a Caídas	1.5 metros
Peso	300g (incl. cable)
Medidas	140mm (L) x 73mm (W) x 70mm (H)
Carcasa	PC + ABS plastic